



BOSSTM XL3

HYDROXYL ODOR PROCESSOR





BOSS XL3™

THE ODOROX® BOSS XL3™ IS THE RIGHT CHOICE FOR LARGE AREA ODOR CONTROL RESULTING FROM FIRES, FLOODING, SEWER BACKUP CONTAMINATION, TOXIC ODORS AND CHEMICAL SPILLS. THIS UNIT IS DESIGNED FOR USE WITH YOUR EXISTING AIR MOVER (AIR MOVER IS NOT INCLUDED).

The Boss XL3™ will provide a heavy concentration of Odorox® hydroxyls to treat large areas affected by fire and smoke, flood, nicotine, grey/black water, decomposition, mold, sewage, chemical spills/off gassing and any other odor problem you may encounter. This unit allows you to decontaminate and deodorize while you dry because it joins directly to your existing air movers. The Boss XL3™ is equipped with a selector switch for 2 or 3 Odorox® hydroxyl generating optics and operates using only 1.6 Amps.

SPECIFICATIONS

Dimensions	11.12" x 20.25" x 20.25" (282.4mm x 514.4mm x 514.5mm)
Weight	25lbs, 11.4kg
Power	120V @ 1.6 Amps
Control	Selector Switch & Pressure Switch which activates from positive air flow
Meter	1/10 quartz hour meter
Mobility	Handle / Rubber feet
Finish	Bronze powder coat
Noise Level	N/A
Number of Optics	3
Air inlet / Outlet	Louvered panel/7" (117.8mm) Spout
Fans & Rating	N/A
Filter	One 9.75" x 10.68" x 0.50" (247.7mm x 271.3mm x 12.7mm)
Certification	ETL Canada/US - CSA & UL Standards Meet or Exceed EPA - OSHA Standard & Guidelines Residual O ³ /Non-accumulative